

tesa® Bath & Shower Anti-Slip Tape - 55533

tesa® Anti Slip Bath & Shower 55533 is a water resistant anti slip tape and ideal for bath tubs and shower tubs. tesa® Anti Slip Bath & Shower 55533 features especially:

- Strong acrylic adhesive
- Easy to apply- simply cut to the needed size with scissors
- Temperature resistant up to 50° C
- UV resistant
- Resistant to cleaning agents
- Tested according to DIN 51097

Main Application

- Waterproof adhesive tape to avoid falls in moist environments
- Perfect for bath tubs and shower tubs

Technical Data & Properties

| | |
|-------------------------------|-------------|
| Dimension | 5m x 25mm |
| Glue | acrylic |
| Colour | transparent |
| Tensile strength | 40 N/cm |
| Elongation at break | 15% |
| Total thickness | 990 µm |
| Adhesion strength | 5,9 N/cm |
| Temperature resistance | 50 °C |
| Water resistance | •••• |
| Ageing resistance (UV) | ••• |
| Resistance to cleaning agents | ••• |

Evaluation across relevant tesa® assortment: •••• very good ••• good •• medium • low

For the latest information on this product please visit <http://www.tesa.com/consumer>

tesa® products prove their impressive quality day in, day out in demanding conditions and are regularly subjected to strict controls. All technical information and data above mentioned are provided to the best of our knowledge on the basis of our practical experience. They shall be considered as average values and are not appropriate for a specification. Therefore tesa SE can make no warranties, expressed or implied, including, but not limited to any implied warranty of merchantability or fitness for a particular purpose. The user is responsible for determining whether the tesa® product is fit for a particular purpose and suitable for the user's method of application. If you are in any doubt, our technical support staff will be glad to support you.

Additional Information & Pictures



55533

For the latest information on this product please visit <http://www.tesa.com/consumer>

tesa® products prove their impressive quality day in, day out in demanding conditions and are regularly subjected to strict controls. All technical information and data above mentioned are provided to the best of our knowledge on the basis of our practical experience. They shall be considered as average values and are not appropriate for a specification. Therefore tesa SE can make no warranties, expressed or implied, including, but not limited to any implied warranty of merchantability or fitness for a particular purpose. The user is responsible for determining whether the tesa® product is fit for a particular purpose and suitable for the user's method of application. If you are in any doubt, our technical support staff will be glad to support you.