



## ANSMANN IL230R

Years Warranty\*

Rechargeable work light for professional use, with multi-functions, robust housing and very bright

### Features

- Professional work light with SMD LED technology
- Additional spotlight in lamp head
- Robust plastic housing with rubberized surface
- One magnet at the bottom of the handle
- Impact protected Li-Ion battery pack (3.7V / 700mAh)
- Charging via USB power supply
- Charge control indication via duo LED
- Luminous flux 230 Lumens (main light) / 135 Lumens (additional spotlight)
- Lighting duration approx. 3,5 hours / 4 hours spotlight
- 2 years ANSMANN Germany warranty



Numéro d'article: 1600-0306  
Contenu de la livraison: Working light, micro-USB charge cable  
Code douanier: 8513100000  
Conditionnement: 8 (177 × 145 × 183 mm)



## Specifications

|                              |                                           |
|------------------------------|-------------------------------------------|
| <b>Illuminant</b>            | LED                                       |
| <b>Illuminant power</b>      | 3 W                                       |
| <b>Light range</b>           | 25 m                                      |
| <b>Luminous flux</b>         | 230 lumens                                |
| <b>Brightness</b>            | 500 Lux                                   |
| <b>Protection class</b>      | IP20                                      |
| <b>Operating time</b>        | 4 h                                       |
| <b>Power supply</b>          | Li-Po (3.7V / 700mAh)                     |
| <b>Light modes</b>           | Haupt-LED: 100% + 50%<br>Zusatz-LED: 100% |
| <b>Colour temperature</b>    | 6500 K                                    |
| <b>Housing material</b>      | ABS + TPE                                 |
| <b>Couleur</b>               | noir / rouge                              |
| <b>Emballage</b>             | boîte en carton                           |
| <b>Operating temperature</b> | -10 - 40 °C                               |
| <b>Storage temperature</b>   | -20 - 30 °C                               |