

## Nelson

|                                   |                                                                             |                         |
|-----------------------------------|-----------------------------------------------------------------------------|-------------------------|
| <b>Teilung</b>                    | 1/4 loop pile                                                               | ISO 2424                |
| <b>Material</b>                   | 100% Wool                                                                   | ISO 2424                |
| <b>Träger</b>                     | Woven                                                                       | ISO 2424                |
| <b>Rueckenausrüstung</b>          | TR (Textilrucken), Filz                                                     | ISO 2424                |
| <b>Bahnbreite</b>                 | 400 cm, 500 cm                                                              | ± 1%<br>EN 984          |
| <b>Oberflächen- / Florgewicht</b> | 1000 gr/m <sup>2</sup>                                                      | ISO 8543                |
| <b>Gesamtgewicht</b>              | TR (Textilrucken) : 1800 gr/m <sup>2</sup><br>Filz : 1850 gr/m <sup>2</sup> | ± 15%<br>ISO 8543       |
| <b>Polhöhe</b>                    | 5 mm                                                                        | ± 2 mm<br>ISO 1766      |
| <b>Totale Höhe / Gesamtdicke</b>  | TR (Textilrucken) : 7 mm<br>Filz : 9 mm                                     | ISO 1765                |
| <b>Noppenzahl</b>                 | 43175/m <sup>2</sup>                                                        | -7.5% .+10%<br>ISO 1763 |
| <b>Brandverhalten</b>             | Cfl-S1                                                                      | EN 13501-1              |
| <b>Verwendungsbereich</b>         | Heavy domestic use (23)                                                     | EN 1307                 |
| <b>Lichtechtheit</b>              | ≥ 5                                                                         | 105-B02                 |
| <b>Reibechtheit</b>               | ≥ 4                                                                         | 105-X12                 |
| <b>Wasserechtheit</b>             | ≥ 4                                                                         | 105-E01                 |

## Teppichsymbole



## Zertifikats

|                                                                                                                                                                                                                                                                                                                                 |                                                                                                                                                                                                                                                                                                                    |
|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <br>2013<br>Condor Carpets<br>Euroweg 3<br>8061 SB Hasselt<br>EN1307<br>DOP: C-027AN095<br>Reaction to fire:<br>Cfl-s1<br>1658<br>Slip resistance: DS<br>TR (Textilrucken)<br>Resilient floor<br>covering to be<br>used within a<br>building | <br>2013<br>Condor Carpets<br>Euroweg 3<br>8061 SB Hasselt<br>EN1307<br>DOP: C-027FN095<br>Reaction to fire:<br>Cfl-s1<br>1658<br>Slip resistance: DS<br>Filz<br>Resilient floor<br>covering to be<br>used within a<br>building |
|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|

