



## ANSMANN Lampe de travail WL400R Slim

Lampe d'atelier rechargeable au format poche pour une utilisation professionnelle

### Features

- Main light and additional light on the lamp head
- Robust plastic housing with rubberised surface
- Housing protection class IP65 / impact resistance IK07
- Lamp handle swivels 180° for flexible light alignment
- Fold-out, 360° rotatable suspension hook and belt clip
- Holding magnet on the underside of the handle
- Permanently installed Li-Po battery pack (3.7V / 1500mAh / 5.55Wh)
- Type-C charging socket / incl. charging cable
- Charging indicator via LED
- Luminous flux: Main LED 400 lumen / Top LED 150 lumen
- Light duration up to 6 hours | charging time: approx. 2.5 hours



Numéro d'article: 1600-0589  
 Contenu du produit: Lampe, câble de chargement USB type C, mode d'emploi  
 Code douanier: 8513100000  
 Conditionnement: 8 (275 × 95 × 193 mm)



## Specifications

|                     |                                                  |                    |                  |               |                    |                |
|---------------------|--------------------------------------------------|--------------------|------------------|---------------|--------------------|----------------|
| Nominal voltage     | 3,7 V                                            |                    |                  |               |                    |                |
| Nominal capacity    | 1500 mAh                                         |                    |                  |               |                    |                |
| Light range         | 25 m                                             |                    |                  |               |                    |                |
| Luminous flux       | 400 lumen                                        |                    |                  |               |                    |                |
| Brightness          | 630 Lux                                          |                    |                  |               |                    |                |
| Protection class    | IP65                                             |                    |                  |               |                    |                |
| Operating time      | 6 h                                              |                    |                  |               |                    |                |
| Power supply        | Li-Po   3.7 V   1500 mAh   5.55 Wh               |                    |                  |               |                    |                |
| Light modes         | Top-LED / COB-LED low power / COB-LED high power |                    |                  |               |                    |                |
| Performance data    | Mode                                             | Colour temperature | Light range      | Luminous flux | Brightness         | Operating time |
|                     | 100%                                             | 6500 K             | 25 m             | 400 lumen     | 630 Lux            | 2,5 h          |
|                     | 30%                                              | 6500 K             | 8 m              | 120 lumen     | 200 Lux            | 6 h            |
|                     | TOP-LED                                          | 7000 K             | 25 m             | 150 lumen     | 630 Lux            | 6 h            |
|                     | 100%                                             |                    |                  |               |                    |                |
| IK Protection Class | IK07                                             |                    |                  |               |                    |                |
| Colour temperature  | 6500 - 7000 K                                    |                    |                  |               |                    |                |
| Illuminant          | Mode                                             | Illuminant         | Illuminant power |               | Colour temperature |                |
|                     | Haupt-Leuchte                                    | COB-LED            | 4 W              |               | 6500 K             |                |
|                     | Top-Leuchte                                      | SMD-LED            | 2 W              |               | 7000 K             |                |
| Housing material    | TPE + PC                                         |                    |                  |               |                    |                |

|                       |             |
|-----------------------|-------------|
| Couleur               | noir / grau |
| Emballage             | Box         |
| Operating temperature | -10 - 40 °C |
| Storage temperature   | -10 - 55 °C |